

Universidad de Sevilla

Consejo Superior de Investigaciones Científicas C/ Américo Vespucio s/n Parque Científico y Tecnológico Cartuja 41092 Sevilla, SPAIN Tel.: +34 954 466 666 www.imse-cnm.csic.es

PhD Grant Funded by the Spanish Ministry of Science, Innovation and Universities

Project: Cognitive Radio Digitizers for IoT Nodes (CORDION) Contact Person: Prof. José M. de la Rosa (jrosa@imse-cnm.csic.es) Reference: PID2019-103876RB-I00 Submission dates: From 13-10-2020 to 27-10-2020 More information at: https://www.ciencia.gob.es/portal/site/MICINN/menuitem.dbc68b34d11ccbd5d52ffeb801432ea0/?vgnextoid=490233572bed4710VgnVCM1000001d04140aRCRD



The so-called Cognitive Radio (CR) technology allows communication systems to make a more efficient use of the electromagnetic spectrum, by dynamically modifying its transmission and reception parameters according to the information sensed from the environment a technique also referred to as spectrum sensing. One of the direct consequences of the physical implementations of CR-based terminals is that the digitizers, i.e the circuits responsible for transforming the signal from the analog to the digital domain, should be placed as close as possible to the antenna, so that most of the hardware is digital and hence, it is easier to program via software. Another key technology enabler for the development of CR-based IoT nodes is the need to embed a certain degree of Artificial Intelligence (AI), so that they can set their specifications in an optimum and autonomous way, according to the environment conditions (communication coverage, spectrum occupancy, intereferences), battery status and energy consumption.

In this scenario, this project aims to address some of the design challenges for the increased in-coming digital-driven world. To this end, AI-managed digitizers for CR-based IoT nodes will be developed. Although the project will cover design considerations of the whole communication system, the physical design will focus on the digitizer, as an essential key building block of IoT devices. For the realization of the proposed digitizer, a 28-nm technology will be used, and a complete demonstrator will be implemented in order to experimentally validate the proposed techniques.



